

# REDUCING TEES & REDUCERS CONCENTRIC AND ECCENTRIC continued

NPS	Outlet or Reduced End		Nominal Center-to-End Tees		Nominal Length of Reducers L	APPROXIMATE WEIGHTS								
	NPS	DN	Run	Outlet		STANDARD WEIGHT		EXTRA STRONG		SCHEDULE 160		DOUBLE EXTRA STRONG		
			C	M		Tee	Reducer	Tee	Reducer	Tee	Reducer	Tee	Reducer	
12	300	#4	10.0	8.50	8.0	101	23.0	132	32	301	-	-	-	
			254	216		203	46	10.4	59	14.5	137	-	-	-
		5	100	10.0	8.50	8.0	105	25.0	134	33	305	72.0	-	67.0
				254	216		203	47	11.3	60	15	139	32.5	-
		6	150	10.0	8.63	8.0	105	28.0	136	34	308	75.0	-	69.0
				254	219		203	47	12.6	61	15.5	140	34	-
		8	200	10.0	9.00	8.0	105	30.0	140	36	315	83.0	-	72.0
				254	229		203	47	13.5	63	16	143	38	-
		10	250	10.0	9.50	8.0	130	32.0	148	39	332	94.0	-	75.0
				254	241		203	59	14.4	67	18	151	43	-
14	350	150	11.0	9.38	13.0	146	58.0	184	59	410	110	-	-	
			279	238		330	66	26	83	27	186	50	-	-
		8	200	11.0	9.75	13.0	147	59.5	187	61	435	125	-	-
				279	248		330	66	27	84	28	197	57	-
		10	250	11.0	10.13	13.0	149	61.0	190	62	470	137	-	-
				29	257		330	67	27	86	28	213	62	-
	12	300	11.0	10.63	13.0	152	64.0	196	75	495	153	-	-	
			279	270		330	68	29	88	34	225	69	-	-
16	400	150	12.0	10.38	14.0	179	-	231	-	540	-	-	-	
			305	264		356	81	-	104	-	245	-	-	-
		8	200	12.0	10.75	14.0	186	69.0	236	89	565	168	-	-
				305	273		356	84	31	106	40	256	76	-
		10	250	12.0	11.13	14.0	196	72.0	248	95	610	190	-	-
				305	283		356	88	32	111	43	277	86	-
	12	300	12.0	11.63	14.0	211	75.0	259	101	675	220	-	-	
			305	295		356	95	34	117	48	340	120	-	-
	14	350	12.0	12.00	14.0	219	80	261	106	750	265	-	-	
			305	305		356	99	36	117	48	340	120	-	-
18	450	200	13.5	11.75	15.0	236	-	302	-	-	-	-	-	
			343	298		381	106	-	136	-	-	-	-	-
		10	250	13.5	12.13	15.0	249	81	311	112	-	-	-	-
				343	308		381	112	36	140	51	-	-	-
		12	300	13.5	12.63	15.0	261	82	332	115	-	-	-	-
				343	321		381	117	37	149	52	-	-	-
	14	350	13.5	13.00	15.0	270	84	340	117	-	-	-	-	
			343	330		381	122	38	153	53	-	-	-	-
	16	400	13.5	13.00	15.0	282	85	352	119	-	-	-	-	
			343	330		381	127	38	158	54	-	-	-	-
20	500	200	15.0	12.75	20.0	294	-	379	-	-	-	-	-	
			381	324		508	133	-	172	-	-	-	-	-
		12	300	15.0	13.13	20.0	307	-	385	-	-	-	-	-
				381	333		508	139	-	175	-	-	-	-
		14	350	15.0	13.63	20.0	316	110	401	149	-	-	-	-
				381	346		508	143	50	182	68	-	-	-
	16	400	15.0	14.00	20.0	329	117	418	153	-	-	-	-	
			381	356		508	149	53	190	69	-	-	-	-
	18	450	15.0	14.00	20.0	341	123	432	158	-	-	-	-	
			381	356		508	155	56	196	72	-	-	-	-
	20	500	15.0	14.50	20.0	355	126	449	165	-	-	-	-	
			381	368		508	161	57	204	75	-	-	-	-
22	550	250	16.5	14.13	20.0	366	-	471	-	-	-	-	-	
			419	359		508	166	-	214	-	-	-	-	-
		12	300	16.5	14.63	20.0	382	-	479	-	-	-	-	-
				419	371		508	173	-	217	-	-	-	-
		14	350	16.5	15.00	20.0	395	128	487	168	-	-	-	-
				419	381		508	179	58	221	76	-	-	-
	16	400	16.5	15.00	20.0	412	133	499	171	-	-	-	-	
			419	381		508	187	60	226	78	-	-	-	-
	18	450	16.5	15.50	20.0	429	140	522	175	-	-	-	-	
			419	394		508	195	64	237	79	-	-	-	-
	20	500	16.5	16.00	20.0	443	143	540	181	-	-	-	-	
			419	406		508	201	65	245	82	-	-	-	-
24	600	250	17.0	15.13	20.0	451	149	556	183	-	-	-	-	
			43	384		508	25	68	252	83	-	-	-	-
		12	300	17.0	15.63	20.0	455	152	562	187	-	-	-	-
				432	397		508	206	69	255	85	-	-	-
	14	350	17.0	16.00	20.0	268	154	571	191	-	-	-	-	
			432	406		508	12	70	259	87	-	-	-	-
	16	400	17.0	16.00	20.0	479	156	585	194	-	-	-	-	
			432	406		508	217	71	285	88	-	-	-	-

INCHES	POUNDS
MILLIMETRES	KILOGRAMS