

REDUCING TEES & REDUCERS CONCENTRIC AND ECCENTRIC continued

NPS	Outlet or Reduced End		Nominal Center-to-End Tees		Nominal Length of Reducers L	APPROXIMATE WEIGHTS							
	NPS	DN	Run	Outlet		STANDARD WEIGHT		EXTRA STRONG		SCHEDULE 160		DOUBLE EXTRA STRONG	
			C	M		Tee	Reducer	Tee	Reducer	Tee	Reducer	Tee	Reducer
24	18	600	17.0	16.50	20.0	490	160	597	198	-	-	-	-
			432	419	508	222	73	271	90	-	-	-	-
	20	500	17.0	17.00	20.0	506	165	614	205	-	-	-	-
			432	432	508	230	75	279	93	-	-	-	-
26	#A12	650	19.5	16.63	□ 24.0	534	-	665	-	-	-	-	-
			495	422	610	242	-	302	-	-	-	-	-
	A14	350	19.5	17.00	□ 24.0	547	-	679	-	-	-	-	-
			495	432	610	248	-	308	-	-	-	-	-
	A16	400	19.5	17.00	24.0	561	-	691	-	-	-	-	-
			495	432	610	254	-	313	-	-	-	-	-
	18	450	19.5	17.50	24.0	575	170	714	215	-	-	-	-
			495	444	610	261	77	324	98	-	-	-	-
	20	500	19.5	18.00	24.0	592	172	733	221	-	-	-	-
			495	457	610	268	78	332	100	-	-	-	-
	22	550	19.5	18.50	24.0	623	174	756	229	-	-	-	-
			495	470	610	283	79	343	104	-	-	-	-
	24	600	19.5	19.00	24.0	643	177	780	235	-	-	-	-
			495	483	610	292	80	354	107	-	-	-	-
30	A14	750	22.0	19.0	□ 24.0	675	-	865	-	-	-	-	-
			559	483	610	305	-	392	-	-	-	-	-
	A16	400	22.0	19.0	□ 24.0	690	-	895	-	-	-	-	-
			559	483	610	313	-	406	-	-	-	-	-
	A18	450	22.0	19.5	□ 24.0	721	-	932	-	-	-	-	-
			559	495	610	327	-	423	-	-	-	-	-
	20	500	22.0	20.0	□ 24.0	744	180	978	264	-	-	-	-
			559	508	610	337	82	444	120	-	-	-	-
	22	550	22.0	20.5	24.0	768	200	1031	270	-	-	-	-
			559	521	610	348	91	468	122	-	-	-	-
	24	600	22.0	21.0	24.0	792	215	1050	275	-	-	-	-
			559	533	610	359	98	476	125	-	-	-	-
	26	650	22.0	21.5	24.0	845	235	1085	282	-	-	-	-
			559	546	610	383	107	492	128	-	-	-	-
36	A16	900	26.5	22.0	□ 24.0	1280	-	1220	-	-	-	-	-
			673	559	610	581	-	553	-	-	-	-	-
	A18	450	26.5	22.5	□ 24.0	1305	-	1310	-	-	-	-	-
			673	572	610	592	-	594	-	-	-	-	-
	A20	500	26.5	23.0	□ 24.0	1360	319	1395	320	-	-	-	-
			673	584	610	617	141	633	145	-	-	-	-
	A22	550	26.5	23.5	□ 24.0	1390	-	146	-	-	-	-	-
			673	597	610	631	-	665	-	-	-	-	-
	24	600	26.5	24.0	24.0	1410	340	1510	360	-	-	-	-
			673	610	610	640	154	685	163	-	-	-	-
	26	650	26.5	24.5	24.0	1425	-	1555	-	-	-	-	-
			673	622	610	646	-	705	-	-	-	-	-
	30	750	26.5	25.0	24.0	1432	375	1595	385	-	-	-	-
			673	635	610	650	170	723	175	-	-	-	-
42	A18	1100	30.0	25.5	24.0	1550	-	1770	-	-	-	-	-
			762	648	610	703	-	803	-	-	-	-	-
	A20	500	30.0	26.0	24.0	1590	-	1810	-	-	-	-	-
			762	660	610	721	-	821	-	-	-	-	-
	A22	550	30.0	26.0	24.0	1630	-	1850	-	-	-	-	-
			762	660	610	739	-	839	-	-	-	-	-
	A24	600	30.0	26.0	24.0	1645	390	1865	405	-	-	-	-
			762	660	610	745	177	846	184	-	-	-	-
	A26	650	30.0	27.5	24.0	1665	425	1890	440	-	-	-	-
			762	698	610	755	193	857	200	-	-	-	-
	30	750	30.0	28.0	□ 24.0	1690	445	1910	465	-	-	-	-
			762	711	610	767	202	866	211	-	-	-	-
	36	900	30.0	28.0	□ 24.0	1710	470	1935	495	-	-	-	-
			762	711	610	776	213	878	225	-	-	-	-

When ordering Reducing Tees, specify the run pipe size first, followed by the outlet size. Example 2 x 2 x 1.

When ordering Reducers, specify the Large End first, followed by the Small End size and the type. Example: 2 x 1 eccentric.

These fittings are also available in other sizes and/or wall thicknesses.

Wall thickness and other pipe size data are in accordance with ASME/ANSI B36.10M.

This size of Reducing Outlet Tee is not covered in ANSI B16.9

△ This size of Reducer is not covered in ANSI B16.9

□ This size of Reducer supplied concentric only.

Tees size 20 NPS (DN 500) and smaller, and Reducers size 24 NPS (DN 600) and smaller. Are normally furnished as seamless Larger size non-seamless Tees and Reducers are produced from X-rayed, stress relieved welded pipe Welds are 100% radiographed in accordance with the requirements of the ASME Boiler & Pressure Vessel Code.

INCHES	POUNDS
MILLIMETRES	KILOGRAMS